

Version 1 Revision Date 07/08/2008 Print Date 07/08/2008

#### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : 75% Acetonitrile / 25% Water - (800)

MSDS Number : 000000013225 Product Use Description : Laboratory Use

Company : Honeywell International Inc.

1953 South Harvey Street Muskegon, MI 49442

For more information call : 1-800-368-0050

(Monday-Friday, 9:00am-5:00pm)

In case of emergency call : Medical: 1-800-498-5701

Transportation: 1-800-424-9300 or +1-703-527-3887

(24 hours/day, 7 days/week)

### **SECTION 2. HAZARDS IDENTIFICATION**

#### **Emergency Overview**

Form : liquid, clear

Color : colourless

Odor : sweet ether-like

Hazard Summary : Flammable. In use, may form flammable/explosive vapour-air

mixture. May be harmful if inhaled. May be harmful if absorbed through skin. May be harmful if swallowed. Irritating to eyes, respiratory system and skin. May cause irritation of the gastrointestinal tract. Can cause fatal cyanide poisoning. May cause convulsions. Symptoms may be delayed. Can be absorbed through skin. Repeated exposure may cause skin

dryness or cracking.

#### **Potential Health Effects**

Skin : Irritating to skin.

Can be absorbed through skin.

May be harmful if absorbed through skin. Can cause fatal cyanide poisoning.

Symptoms may be delayed.

Prolonged or repeated skin contact with liquid may cause defatting resulting in drying, redness and possible blistering.

Eyes : Irritating to eyes.



Version 1 Revision Date 07/08/2008 Print Date 07/08/2008

Causes itching, burning, redness and tearing.

Ingestion : Ingestion may cause gastrointestinal irritation, nausea,

vomiting and diarrhoea.

May cause systemic poisoning with symptoms paralleling those

of inhalation.

Can cause fatal cyanide poisoning.

Symptoms may be delayed.

Inhalation : Causes respiratory tract irritation.

Inhalation of high vapour concentrations can cause

CNS-depression and narcosis.

Causes headache, drowsiness or other effects to the central

nervous system.

Can cause fatal cyanide poisoning.

Symptoms may be delayed.

Chronic Exposure : Can cause fatal cyanide poisoning.

Causes damage to the kidneys/liver/eyes/brain/respiratory system/central nervous system through prolonged or repeated

exposure.

Prolonged or repeated skin contact with liquid may cause defatting resulting in drying, redness and possible blistering.

**Aggravated Medical** 

Condition

: People suffering from pre-existing thyroid conditions may

experience adverse effects.

Neurological disorders

Heart disease

Respiratory disorders

Liver disorders Kidney disorders Skin disorders Eye disorders

Target Organs : Respiratory system

Cardiovascular system Central nervous system

Liver Kidney

#### Carcinogenicity

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, or OSHA.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Component CAS-No. Weight %



Version 1 Revision Date 07/08/2008 Print Date 07/08/2008

Acetonitrile 75-05-8 70.20 Water 7732-18-5 29.80

#### **SECTION 4. FIRST AID MEASURES**

Inhalation : Remove to fresh air. If not breathing, give artificial respiration. If

breathing is difficult, give oxygen. Use oxygen as required, provided a qualified operator is present. Call a physician.

Skin contact : Wash off immediately with plenty of water for at least 15

minutes. Take off contaminated clothing and shoes immediately. Wash contaminated clothing before re-use. Call a physician.

Eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes. Call a physician.

Ingestion : Call a physician. Immediate medical attention is required. Do not

induce vomiting without medical advice. Never give anything by

mouth to an unconscious person.

Notes to physician

Treatment : Treat as cyanide poisoning. Symptoms of poisoning may not

appear for several hours. Keep under medical supervision for at

least 48 hours.

#### **SECTION 5. FIRE-FIGHTING MEASURES**

Flash point : 8.89 °C (48.00 °F)

closed cup

Lower explosion limit : not determined

Upper explosion limit : not determined

Suitable extinguishing

media

Carbon dioxide (CO2)

Dry chemical

Alcohol-resistant foam

Cool closed containers exposed to fire with water spray.

Extinguishing media which shall not be used for safety

reasons

: Do not use a solid water stream as it may scatter and spread

fire.

Specific hazards during fire

fighting

: Flammable.

Vapours may form explosive mixtures with air.

Vapours are heavier than air and may spread along floors.



Version 1 Revision Date 07/08/2008 Print Date 07/08/2008

Vapors may travel to areas away from work site before

igniting/flashing back to vapor source.

In case of fire hazardous decomposition products may be

produced such as:

Hydrogen cyanide (hydrocyanic acid)

Carbon dioxide (CO2), carbon monoxide (CO), oxides of

nitrogen (NOx), dense black smoke.

Special protective equipment for fire-fighters

Wear self-contained breathing apparatus and protective suit.

### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions : Wear personal protective equipment.

Immediately evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

Ensure adequate ventilation. Remove all sources of ignition.

Do not swallow.

Avoid breathing vapors, mist or gas. Avoid contact with skin, eyes and clothing.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Discharge into the environment must be avoided.

Do not flush into surface water or sanitary sewer system.

Prevent product from entering drains.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Methods for cleaning up : Ventilate the area.

No sparking tools should be used. Use explosion-proof equipment.

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations

(see section 13).

## **SECTION 7. HANDLING AND STORAGE**

#### Handling

Handling : Wear personal protective equipment.

Use only in well-ventilated areas. Keep container tightly closed.

Do not smoke. Do not swallow.

Avoid breathing vapors, mist or gas. Avoid contact with skin, eyes and clothing.



Version 1 Revision Date 07/08/2008 Print Date 07/08/2008

Advice on protection against :

fire and explosion

Keep away from fire, sparks and heated surfaces.

Take precautionary measures against static discharges.

Ensure all equipment is electrically grounded before beginning

transfer operations.

Use explosion-proof equipment.

Keep product and empty container away from heat and sources

of ignition.

No sparking tools should be used.

No smoking.

## **Storage**

Requirements for storage areas and containers

Store in area designed for storage of flammable liquids. Protect

from physical damage.

Keep containers tightly closed in a dry, cool and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Keep away from heat and sources of ignition.

Keep away from direct sunlight.

Store away from incompatible substances.

Container hazardous when empty.

Do not pressurize, cut, weld, braze, solder, drill, grind or expose

containers to heat or sources of ignition.

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Protective measures : Ensure that eyewash stations and safety showers are close to

the workstation location.

Engineering measures : Use with local exhaust ventilation.

Prevent vapor buildup by providing adequate ventilation during

and after use.

Eye protection : Do not wear contact lenses.

Wear as appropriate:

Safety glasses with side-shields If splashes are likely to occur, wear:

Goggles or face shield, giving complete protection to eyes

Hand protection : Solvent-resistant gloves

Gloves must be inspected prior to use.

Replace when worn.

Skin and body protection : Wear as appropriate:

Solvent-resistant apron

Flame retardant antistatic protective clothing

If splashes are likely to occur, wear:



Version 1 Revision Date 07/08/2008 Print Date 07/08/2008

Protective suit

Respiratory protection : In case of insufficient ventilation wear suitable respiratory

equipment.

For rescue and maintenance work in storage tanks use

self-contained breathing apparatus.

Use NIOSH approved respiratory protection.

Hygiene measures : When using, do not eat, drink or smoke.

Wash hands before breaks and immediately after handling the

product.

Keep working clothes separately.

Remove and wash contaminated clothing before re-use.

Do not swallow.

Avoid breathing vapors, mist or gas. Avoid contact with skin, eyes and clothing.

**Exposure Guidelines** 

Acetonitrile 75-05-8 ACGIH TWA 20 ppm

Skin designation:

Can be absorbed through the skin.

NIOSH REL 20 ppm 34 mg/m3

US CA OEL TWA PEL 40 ppm 70 mg/m3

US CA OEL STEL 60 ppm 105 mg/m3

Skin designation:

Can be absorbed through the skin.

OSHA Z1 PEL 40 ppm 70 mg/m3

OSHA Z1A TWA 40 ppm 70 mg/m3

OSHA Z1A STEL 60 ppm 105 mg/m3

### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Form : liquid, clear

Color : colourless

Odor : sweet ether-like

pH : 7.8

Page 6 / 10



Version 1 Revision Date 07/08/2008 Print Date 07/08/2008

Boiling point/boiling range : 66.67 °C (152.01 °F)

Vapor pressure : 97.325 hPa

at 20 °C (68 °F)

The physical data is that of the main component.

Density : 0.8478 g/cm3

at 20 °C (68 °F)

#### **SECTION 10. STABILITY AND REACTIVITY**

Conditions to avoid : Heat, flames and sparks.

Keep away from direct sunlight.

Materials to avoid : Acids

Bases

Oxidizing agents Reducing agents

Sulfites Perchlorates

May attack many plastics, rubbers and coatings.

Hazardous decomposition

products

: In case of fire hazardous decomposition products may be

produced such as:

Hydrogen cyanide (hydrocyanic acid)

Carbon dioxide (CO2), carbon monoxide (CO), oxides of

nitrogen (NOx), dense black smoke.

Hazardous reactions : Hazardous polymerisation does not occur.

Stable under normal conditions.

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

Acute oral toxicity : LD50 rat

Dose: 2,460 mg/kg

Test substance: Acetonitrile

Acute dermal toxicity : LD50 rabbit

Dose: > 2,000 mg/kg

Test substance: Acetonitrile

Acute inhalation toxicity : LC50 rat

Dose: 7551 ppm

Exposure time: 8 h

Test substance: Acetonitrile



Version 1 Revision Date 07/08/2008 Print Date 07/08/2008

### **SECTION 12. ECOLOGICAL INFORMATION**

Toxicity to fish : flow-through test LC50

Species: Pimephales promelas (fathead minnow)

Dose: 1,640 mg/l Exposure time: 96 h

Test substance: Acetonitrile

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

Waste Information: Observe all Federal, State, and Local Environmental regulations.

#### **SECTION 14. TRANSPORT INFORMATION**

**DOT** UN-Number : 1648

Proper shipping name : Acetonitrile solution

Class 3
Packing group II
Hazard Label 3

IATA UN Number : 1648

Description of the goods : Acetonitrile solution

Class : 3
Packaging group : II
Hazard Label : 3
Packing instruction (cargo : 307

aircraft)

Packing instruction : 305

(passenger aircraft)

Packing instruction : Y305

(passenger aircraft)

IMDG Substance No. : UN 1648

Description of the goods : Acetonitrile solution

Class : 3
Packaging group : II
Hazard Label : 3
EmS Number : F-E
Marine pollutant : no

## **SECTION 15. REGULATORY INFORMATION**



Version 1 Revision Date 07/08/2008 Print Date 07/08/2008

**Inventories** 

**EU. EINECS** : On the inventory, or in compliance with the inventory

US. Toxic Substances

Control Act

: On TSCA Inventory

Australia. Industrial

Chemical (Notification and

Assessment) Act

: On the inventory, or in compliance with the inventory

: All components of this product are on the Canadian DSL list.

Canada. Canadian **Environmental Protection** Act (CEPA). Domestic Substances List (DSL).

(Can. Gaz. Part II, Vol. 133)

Japan. Kashin-Hou Law List : On the inventory, or in compliance with the inventory

Korea. Toxic Chemical Control Law (TCCL) List : On the inventory, or in compliance with the inventory

Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act

: On the inventory, or in compliance with the inventory

China. Inventory of Existing

**Chemical Substances** 

: On the inventory, or in compliance with the inventory

Switzerland, Consolidated

Inventory

: On the inventory, or in compliance with the inventory

New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New

Zealand

: On the inventory, or in compliance with the inventory

TSCA 12B : US. Toxic Substances Control Act (TSCA) Section 12(b) Export

Notification (40 CFR 707, Subpt D)

Acetonitrile 75-05-8

**National regulatory information** 

**SARA 313 Components** : Acetonitrile 75-05-8

SARA 311/312 Hazards : Fire Hazard

> Acute Health Hazard Chronic Health Hazard



Version 1 Revision Date 07/08/2008 Print Date 07/08/2008

**CERCLA Reportable** 

Quantity

: 7123 lbs

California Prop. 65 : WARNING! This product contains a chemical known in the State

of California to cause cancer.

Acrylonitrile 107-13-1

Massachusetts RTK : Acetonitrile 75-05-8

New Jersey RTK : Acetonitrile 75-05-8

Pennsylvania RTK : Acetonitrile 75-05-8

WHMIS Classification : B2

D1A D2B

#### **SECTION 16. OTHER INFORMATION**

HMIS III NFPA
Health Hazard : 2\* 2
Flammability : 3 3

Physical Hazard : 0

Instability : 0

### **Further information**

\* - Chronic health hazard